

HEAT KING


HK 1500 THE CUBE GLYCOL HEATING SYSTEM



FEATURES

- 1.5 MILLION BTU/HR
- THAW UP TO 34,000 FT²
- CURE UP TO 68,000 FT²
- CONNECT 15-100,000 OR 8-200,000 BTU/HR HEAT EXCHANGERS
- PUMP UP TO 30 FLOORS - NO BOOSTER PUMP OR RESERVOIR REQUIRED
- AVAILABLE IN DIESEL, LP OR NG
- 245 GALLON GLYCOL TANK & STANDARD ON BOARD AIR COMPRESSOR TO EVACUATE ALL GLYCOL IN HOSES
- CSA/UL CERTIFIED
- PLC CONTROLLED SYSTEM

MODULAR DESIGN



HK1500 SPECIFICATIONS

<ul style="list-style-type: none"> • Hose • Hose Reel • Supply Manifold • Return Manifold • Ground Thawing Capacity • Concrete Curing Capacity • Temporary Heating Capacity • Field Pump • Circulating Pump 	<p>USE UP TO 24- 700 ft Field Hoses (5/8" Hose) Portable Hose Reels Required 4 - 1" Quick Disconnects, 2" Camlock 4 - 1" Quick Disconnects, 2" Camlock Up to 34,000 ft² Up to 68,000 ft² Up to 1,400,000 cubic feet 1- 7.5 Hp Multistage Centrifugal 2- 1.5 Hp Centrifugal</p>	<ul style="list-style-type: none"> • Heater Capacity Diesel • Heater Capacity LP/NG • Glycol Tank • Electrical Requirements • Nominal Power • Dimensions • Weight (Full of Glycol) <p>No Fuel tank included-</p>	<p>1,500,000 BTU/H Heating Fuel Input 1,400,000 BTU/H 950 L/ 245 US Gal 208 VAC 3 PHASE x 40A 12.2 KVA 3x208 VAC/60 Hz 7'4"x7'4"x6' 4800 lbs/2179 kg</p>
--	--	---	--